


TPC-2140WP

21.5" Full HD TFT LCD Touch Panel
Computer with AMD Dual-core processor



Features

- 21.5" Full HD TFT LED LCD display
- AMD dual-core T56E 1.65GHz with independent GPU, advanced graphical performance
- 16:9 wide screen with PCT multi-touch
- Built-in function and home key button used for intuitive UI
- Anti-scratch surface: 7H hardness
- Easy Maintenance of Cfast/HDD/Mini-PCIe components by opening side cover
- Support Mini-PCIe expansion slot
- Support HDMI for second display application
- HD Audio supports for alarm application
- Front LED indicator to show operating status
- IP66 compliant true flat screen
- Compact design with Die-cast Magnesium alloy front bezel
- Fanless cooling system
- Winner of the 2013 iF product design award

Introduction

With a brand-new ID design, the TPC-2140WP provides a high resolution 21.5" display and PCT multi-touch in 16:9 wide format. By embedding an AMD T56E 1.65GHz processor with independent GPU, the TPC-2140WP can support advanced graphical performance in more complex applications. Built-in function and home key button for greater user usability and operating safety. The TPC-2140WP also supports a mini-PCIe slot for communication function expansion. The opening side cover is designed for easy maintenance of Cfast/HDD/Mini-PCIe components.

Specifications

General

- BIOS**: AMI 32Mbit
- Certification**: BSMI, CCC, CE, FCC Class A, UL
- Cooling System**: Fanless design
- Dimensions (W x H x D)**: 558.4 x 349.8 x 56.7 (21.98" x 13.77" x 2.23")
- Enclosure**: Front bezel: Die-cast Magnesium alloy
Backhousing: PC/ABS Resin
- Mounting**: Panel Mount
- OS Support**: Microsoft® Win8/WES7P/XP/WES2009
- Power Consumption**: 35 W Typical
- Power Input**: 18 ~ 32 V_{DC}
- Watchdog Timer**: 1 ~ 255 sec (system)
- Weight (Net)**: 8.5 kg (18.74 lbs)

System Hardware

- CPU**: AMD G-series T56E 1.65GHz
- Chipset**: AMD A50M FCH
- Memory**: 4GB SO-DIMM DDR3 SDRAM
- LAN**: 10/100/1000Base-T x 2
- Expansion Slots**: Full-sized Mini-PCI-E x 1
- Storage**: CFast slot x 1
2.5" SATA HDD x 1 (optional)
- I/O**: RS-232 x 3
RS-422 / 485 x 1
USB 2.0 x 2 (Host)
HDMI x 1
Mic in x 1, Line out x 1

LCD Display

- Display Type**: Full HD TFT LED LCD
- Display Size**: 21.5"
- Max. Resolution**: 1920 x 1080
- Max. Colors**: 16.7 M
- Luminance cd/m²**: 300
- Viewing Angle (H/V°)**: 178/178
- Backlight Life**: 50,000 hrs


Touchscreen

- Light Transmission**: ≥88%
- Resolution**: 4096*4096 dot
- Type**: Projected capacitive


Environment

- Humidity**: 10 ~ 95% RH @ 40°C, non-condensing
Note: Tested for 48hrs
- Ingress Protection**: Front panel: IP66
- Operating Temperature**: 0 ~ 55°C (32 ~ 131°F)
- Storage Temperature**: -20 ~ 60°C (-4 ~ 140°F)
- Vibration Protection**: With HDD: 1 Grms (5 ~ 500 Hz)
(Operating, random vibration)

Rear View



- a. COM 1 & 2 (RS-232)
- b. Audio (Line out, Mic in)
- c. HDMI
- d. USB 2.0
- e. LAN (10/100/1000)
- f. Power Receptor
- g. COM3 (RS-232)
- g². COM4 (RS-422/485)
- h. Mini-PCI-E slot
- i. 2.5" SATA HDD Housing



Ordering Information

- TPC-2140WP-T3AE 21.5" full-HD Multi-Touch Panel PC, AMD T56E, 4GB

- WA-ST2140W-G15H4AE TPC-2140WP-T3AE, SCADA Runtime 1500 tags, 1TB HDD, WES7P

Optional Accessory

- PWR-247-CE 60W DC 24V/2.5A Output Power Supply
- 1702002600 Power Cord 3P UL/CSA 125V 10A 1.83M
- 1702002605 Power cable EU Plug 1.8M
- 1702031801 Power cable UK Plug 1.8M
- 1700000596 Power cable China/Australia Plug 1.8M

Embedded O/S

- 2070012384 TPC-xx40WP WS7P x86 MUI Image v4.12

S/W Bundle Offering

- WA-HT2140W-G15H1AE TPC-2140WP-T3AE, HMI Runtime 1500 tags, 32G CFast, WES7P

Application Software

<p>WebAccess/SCADA</p>	<p>Advantech WebAccess is a 100% web based SCADA (Supervisory Control And Data Acquisition) software and it acts as an IIoT Platform providing open interfaces for partners to develop IoT applications for different vertical markets. In addition to traditional SCADA functions, WebAccess has an intelligent Dashboard, to provide users with cross-platform, cross-browser data analysis and user interface using HTML5 technology. As well as the built-in widgets, WebAccess also provides Widget Builder to allow customers to build their own.</p>
<p>WebAccess/HMI</p>	<p>WebAccess/HMI is Human Machine Interface (HMI) software based on Microsoft's Windows operating system. It utilizes a PC's ample resources, ie speed, storage, multimedia, peripheral devices, and large screen to produce a complex human-machine interface. WebAccess/HM with its communication and monitoring ability supports more than 350 PLC communication protocols and a wide choice of screen design objects, to satisfy multiple integrations of factory automation and all-round human-machine interface operation and monitoring requirements.</p>